



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 286-007
Product name **General Purpose Degreaser**
Effective date 04-Mar-2011
Company information Sprayway Inc
1005 Westgate Drive
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 06
Supersedes date 04-Mar-2011

2. Hazards Identification

Emergency overview Aerosol. FLAMMABLE
Will be easily ignited by heat, spark or flames. CONTENTS UNDER PRESSURE.
Prolonged exposure may cause chronic effects. Irritating to eyes.

Potential health effects

Routes of exposure Inhalation. Skin contact. Ingestion.

Eyes Contact with eyes may cause irritation.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Coughing. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	30 - 40
Diethylene Glycol Monobutyl Ether	112-34-5	20 - 30
Acetone	67-64-1	10 - 15
d-Limonene	5989-27-5	8 - 10
Ethoxylated Alcohol	34398-01-1	3 - 5
Carbon Dioxide	124-38-9	1 - 3
Non-hazardous and other components below reportable levels		10 - 20

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off with warm water and soap. Get medical attention if irritation develops and persists. Immediately take off all contaminated clothing.

Inhalation

Move to fresh air. Get medical attention immediately.

Ingestion

If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not induce vomiting without advice from poison control center. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Notes to physician

Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Water. Water spray. Water fog. Alcohol foam. Dry chemical. Carbon dioxide (CO2).

Protection of firefighters

Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out.

6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components

CAS #

TWA

STEL

Ceiling

Diethylene Glycol Monobutyl Ether 112-34-5

20 ppm

Not established

Not established

Acetone

67-64-1

500 ppm

750 ppm

Not established

Ethoxylated Alcohol

34398-01-1

50 ppm

Not established

Not established

Carbon Dioxide

124-38-9

5000 ppm

30000 ppm

Not established

OSHA

Components

CAS #

TWA

STEL

Ceiling

Diethylene Glycol Monobutyl Ether 112-34-5

100 ppm

Not established

Not established

Acetone

67-64-1

1000 ppm

Not established

Not established

Ethoxylated Alcohol

34398-01-1

200 ppm

Not established

300 ppm

Carbon Dioxide

124-38-9

5000 ppm

Not established

Not established

Personal protective equipment

Eye / face protection

Chemical goggles are recommended.

Skin protection

Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	368.6 °F (187.2 °C) estimated
Color	Clear. Colorless.
Density	0.897 g/cm ³ estimated
Flammability (HOC)	32.3842 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	Solvent.
pH	Not applicable
Physical state	Liquid.
Pressure	60 - 70 psig @ 70F
Solubility	Partially
Specific gravity	0.8971 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Instability caused by elevated temperatures. Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Acute effects	Acute LD50: 3166 mg/kg estimated, Rat, Dermal Acute LC50: 12 mg/l/4h estimated, Rat, Inhalation
Component analysis - LD50	
Toxicology Data - Selected LD50s and LC50s	
Acetone	67-64-1 Oral LD50 Rat 5800 mg/kg
Diethylene Glycol Monobutyl Ether	112-34-5 Oral LD50 Rat 3384 mg/kg; Dermal LD50 Rabbit 2700 mg/kg
d-Limonene	5989-27-5 Oral LD50 Rat 4400 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
Synthetic Isoparaffinic Hydrocarbon	64742-47-8 Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
Teratogenicity	Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity	LC50 118 mg/L, Fish, 96.00 Hours, EC50 5378 mg/L, Daphnia, 48.00 Hours, IC50 1981 mg/L, Algae, 72.00 Hours, Contains a substance which causes risk of hazardous effects to the environment.
-------------	--

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	None



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Diethylene Glycol Monobutyl Ether 112-34-5

1.0 % de minimis concentration (applies to R-(OCH₂CH₂)_n-OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories (311/312)
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Acetone	67-64-1	Environmental hazard
Carbon Dioxide	124-38-9	Present
Diethylene Glycol Monobutyl Ether	112-34-5	Environmental hazard
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Present

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 4
Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process,

MSDS sections updated

Product and Company Identification: Product and Company Identification
Composition / Information on Ingredients: Ingredients
First Aid Measures: Inhalation
Physical & Chemical Properties: Physical & Chemical Properties
Transport Information: Agency Name and Packaging Type/Transport Mode Selection

Prepared by

Regulatory Compliance